# Safety Data Sheet



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name:

SikaBond®-TF Plus N

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor : Sika Limited

Watchmead Welwyn Garden City

Hertfordshire. AL7 1BQ

United Kingdom

Telephone no. : 01707 394444 Fax no. : 01707 329129 e-mail address of person

responsible for this SDS

: EHS@uk.sika.com

: +44 (0)1707 363899 (available during office hours). **Emergency telephone number** 

#### 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R42

**Human health hazards** : May cause sensitisation by inhalation.

Additional warning phrases : Contains isocyanates. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ : Filled PUR-polymer **Characteristics** 

Ingredient name	CAS number	%	EC number	Classification
4,4'-methylenediphenyl diisocyanate	101-68-8	0.1-1	202-966-0	Carc. Cat. 3; R40 [1] [2] Xn; R20, R48/20 Xi; R36/37/38 R42/43
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

: 26.11.2010. Date of issue **MSDS no.** : 600252 1/6 SikaBond®-TF Plus N 26.11.2010 2/6

# 4. FIRST AID MEASURES

#### First-aid measures

**Inhalation** : Get medical attention if adverse health effects persist or are severe. Get medical

attention if symptoms appear.

**Ingestion**: Do not induce vomiting unless directed to do so by medical personnel. Maintain an

open airway. Seek immediate medical attention.

**Skin contact**: Wash contaminated skin with soap and water. Remove contaminated clothing and

shoes. Continue to rinse for at least 10 minutes. Get medical attention if symptoms

occur.

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

# 5. FIRE-FIGHTING MEASURES

## **Extinguishing media**

**Suitable**: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

halogenated compounds

metal oxide/oxides

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Keep unnecessary and unprotected personnel from entering. Do not touch or walk

through spilt material. Put on appropriate personal protective equipment (see section

8).

**Environmental precautions**: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-

combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13).

**Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container.

# 7. HANDLING AND STORAGE

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Date of issue : 26.11.2010. MSDS no. : 600252 2/6

SikaBond®-TF Plus N 26.11.2010 3/6

# 7. HANDLING AND STORAGE

#### Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

## **Packaging materials**

Recommended

: Use original container.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure limit values**

#### Ingredient name

4,4'-methylenediphenyl diisocyanate

## Occupational exposure limits

EH40/2005 WELs (United Kingdom (UK), 8/2007). Skin sensitiser.

Notes: as NCO

STEL: 0.07 mg/m³, (as NCO) 15 minute(s). TWA: 0.02 mg/m³, (as NCO) 8 hour(s).

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

# Occupational exposure controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

organic vapour filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm SikaBond®-TF Plus N 26.11.2010 4/6

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### **General information**

**Appearance** 

Form : Paste.

Colour : Various.

Odour : Characteristic.

#### Important health, safety and environmental information

Flash point : Closed cup: >100°C (>212°F)

Density : ~1.26 g/cm³ [20°C (68°F)]

Solubility : Insoluble in the following materials: water Viscosity : Dynamic: 80000 mPa·s (80000 cP)

# 10. STABILITY AND REACTIVITY

Stability : The product is stable.

Conditions to avoid : No specific data.

Materials to avoid : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# 11. TOXICOLOGICAL INFORMATION

#### Potential acute health effects

Inhalation: May cause sensitisation by inhalation.Ingestion: Can cause gastrointestinal disturbances.

Skin contact: May cause skin irritation.Eye contact: May cause eye irritation.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

## 12. ECOLOGICAL INFORMATION

**Environmental effects** 

: Avoid contact of spilt material and runoff with soil and surface waterways. Do not empty into drains; dispose of this material and its container in a safe way.

# 13. DISPOSAL CONSIDERATIONS

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Empty

containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

European waste catalogue

(EWC)

: 08 04 09\* waste adhesives and sealants containing organic solvents or other

dangerous substances

Packaging :

Date of issue : 26.11.2010. MSDS no. : 600252 4/6

SikaBond®-TF Plus N 26.11.2010 5/6

#### **DISPOSAL CONSIDERATIONS** 13.

Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10\* packaging containing residues of or contaminated by dangerous substances

#### 14. TRANSPORT INFORMATION

### **International transport regulations**

**ADR** 

Not regulated.

**IMDG** 

Not regulated.

Marine pollutant : No

**IATA** 

Not regulated.

#### **15**. REGULATORY INFORMATION

## EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xn

Harmful

**Contains** : 4,4'-methylenediphenyl diisocyanate

Risk phrases : R42- May cause sensitisation by inhalation. : S23- Do not breathe gas/fumes/vapour/spray Safety phrases

S45- In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

Additional warning phrases: Contains isocyanates. See information supplied by the manufacturer.

: VOC (w/w): 1.07% **VOC** content (EU)

**National regulations** 

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP

Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as

amended)

Health & Safety at Work Act 1974

The Environmental Protection (Duty of Care) Regulations 1991

Hazardous waste regulations 2005

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2007

**Guidance Publications** : Approved Code of Practice - Management of Health and Safety at Work, HSE

General Approved Code of Practice to COSHH Regulations, HSE.

EH40, Workplace Exposure Limits, HSE (as updated).

HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.

: 26.11.2010. Date of issue **MSDS no.** : 600252 5/6 SikaBond®-TF Plus N 26.11.2010 6/6

#### 16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and : R40- Limited evidence of a carcinogenic effect.

R20- Harmful by inhalation.

R48/20- Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R36/37/38- Irritating to eyes, respiratory system and skin.

R42- May cause sensitisation by inhalation.

R42/43- May cause sensitisation by inhalation and skin contact.

Full text of classifications referred to in sections 2 and : Carc. Cat. 3 - Carcinogen category 3

Xn - Harmful Xi - Irritant

**History** 

Date of printing : 26.11.2010. Date of issue 26.11.2010.

Date of previous issue : No previous validation.

#### **Notice to reader**

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

: 26.11.2010. MSDS no. : 600252 Date of issue 6/6